

INSTRUCTIONS

Specifications:

Image Sensor:	1/3" High Res. CCD
Picture Elements:	NTSC: 768x494
Resolution:	540 lines
S/N Ratio:	More than 48 dB
Min Illumination:	0.02 LUX @ F1.2
Electronic Shutter:	1/60s - 1/100,000s, ON/OFF Switch-able
Iris Control:	Built-in DC Drive Iris Control
Flickerless Mode:	1/60s ON/OFF switchable
Gain Control:	High/Low switchable
Auto White Balance:	Color Temperature: 2500K-9500K
Back Light Comp.:	ON/OFF switchable
Gamma Characteristic:	0.45
Camera Lens:	Vari-Focal with DC Drive Iris Lens
Focal Length & App. Ratio:	3.7mm-12mm, F1.6-3.0
Angle of View:	Wide:H83.9°V61.9°, Tele:H23.0°V17.9°
Sync. System:	Internal, Negative sync.
Power Requirements:	12VDC
Power Consumption:	75 mA
Video Output:	1 Vp-p @ 75 ohms
Dimensions:	dia. 4.20", Height 3.56"
Operating Temp:	-10°C to 50°C (14°F to 122°F)

Specifications subject to change without notice.

CHANNEL VISION Limited Warranty

Channel Vision Technology will repair or replace any defect in material or workmanship which occurs during normal use of this product with new or rebuilt parts, free of charge in the USA, for two years from the date of original purchase. This is a no hassle warranty with no mail in warranty card needed. This warranty does not cover damages in shipment, failures caused by other products not supplied by Channel Vision Technology, or failures due to accident, misuse, abuse, or alteration of the equipment. This warranty is extended only to the original purchaser, and a purchase receipt, invoice, or other proof of original purchase date will be required before warranty repairs are provided.

Mail in service can be obtained during the warranty period by calling (800) 840-0288 toll free. A Return Authorization number must be obtained in advance and can be marked on the outside of the shipping carton.

This warranty gives you specific legal rights and you may have other rights (which vary from state to state). If a problem with this product develops during or after the warranty period, please contact Channel Vision Technology, your dealer or any factory-authorized service center.



6105 Medium Color Dome Camera

 CHANNEL VISION™


©2010 CHANNEL VISION TECHNOLOGY

Model 6105



The **6105** is a color dome camera. Its vari-focal lens allows the field of view to be adjusted for almost any application, while its mounting flexibility and unobtrusive design make it perfect for residential use.

Features:

- High quality 1/3" High Resolution CCD sensor
- Vari-focal Lens
- Digital Signal Processor (DSP) chip-set provides image control
- High sensitivity, low smear, high anti-blooming and high S/N ratio
- Automatic Gain Control (AGC) and Auto White Balance (AWB)
- 3-Axis mechanism for easy rotation and adjustment



Adjusting the 3-Axis Mount



Installation:

- Rotate the dome housing counterclockwise to remove it from the base.
- Drill a hole in the wall or ceiling for wiring (see diagram).
- If necessary, attach the camera's video output to a coax extension that is long enough to reach your monitor or video distribution equipment.
- If necessary, cut the connector off of the end of the power supply and splice in an extension using crimp-on connectors.
- Mount the base with the provided screws.
- Move the camera body to adjust the view and make electronic adjustments using the dip switches.
- Attach the dome and rotate it clockwise to secure it.