

● CHANNEL VISION™

10 Year Limited Warranty

Channel Vision Technology will repair or replace any defect in material or workmanship which occurs during normal use of this product with new or rebuilt parts, free of charge in the USA, for ten years from the date of original purchase. This is a no hassle warranty with no mail in warranty card needed. This warranty does not cover damages in shipment, failures caused by other products not supplied by Channel Vision Technology, or failures due to accident, misuse, abuse, or alteration of the equipment. This warranty is extended only to the original purchaser, and a purchase receipt, invoice, or other proof of original purchase date will be required before warranty repairs are provided.

Mail in service can be obtained during the warranty period by calling (800) 840-0288 toll free. A Return Authorization number must be obtained in advance and can be marked on the outside of the shipping carton.

This warranty gives you specific legal rights and you may have other rights (which vary from state to state). If a problem with this product develops during or after the warranty period, please contact Channel Vision Technology, your dealer or any factory-authorized service center.

● CHANNEL VISION™
channelvision.com

234 Fischer Avenue, Costa Mesa, California 92626
(714)424-6500 • (800)840-0288 • (714)424-6510 fax

500-247 rev A

INSTRUCTIONS



IC624 6.5" IN-CEILING SPEAKER

ARIA™
BY ● CHANNEL VISION™


©2010 CHANNEL VISION TECHNOLOGY

Model IC624

Channel Vision's ARIA™ **IC624** 6.5" in-ceiling custom installation speakers feature high power handling capability providing true stereo quality sound and not simply background music. The 15° angled woofer and pivoting tweeter can be aimed to any position to custom fit any room, making these speakers perfect for home theater and whole-house audio applications. High quality materials ensure long life and great performance. Gold speaker wire terminals not only provide better contact surface but also offer less resistance to signal transfer for a clearer sound.

Features:

- 6.5" High performance in-ceiling loudspeaker
- High power handling capacity
- Recommended power: 20W to 160W (peak)
- 15° Angled woofer
- Gold speaker terminals
- Pivoting tweeter technology with 1" voice coil.
- Kevlar woofer with butyl rubber surround
- Small perforated designer grill



Installation:

- Use the provided template to mark and cut a 8.25" hole in drywall away from ceiling joists.
- We recommend AWG 16 stranded wire or larger.
- For proper phasing, both speakers must be wired alike. Connect red wires to red terminals on the speakers and to red or plus terminals on the amplifier.
- Install IC624 in the hole. Tighten the mounting screws. The mounting "dogs ears" will rotate outward and grip the drywall. **DO NOT OVER TIGHTEN** the screws. A battery operated drill on a "low clutch" setting is recommended.
- Aim tweeter
- To control the volume of the speaker locally, use an impedance matching volume control, such as the Channel Vision VC-302.

Specifications:

Frequency range:	50Hz - 22kHz ± 6dB
Crossover:	12dB/octave (low pass) 12dB/octave (high pass)
Sensitivity:	89dB (1W/1m)
Power Handling:	160 Watts peak
Drivers:	1- 1" Neodymium pivoting soft dome tweeter 1- 15° Angled 6.5" Kevlar woofer
Magnet:	16-ounce ferrite magnet
Impedance:	8 ohms
Finish:	ABS plastic
Dimensions:	9" OD. 4" height (from surface of wall board) hole size: 8.25" diameter

Specifications subject to change without notice.