

10 Year Limited Warranty

Channel Vision Technology will repair or replace any defect in material or workmanship which occurs during normal use of this product with new or rebuilt parts, free of charge in the USA, for ten years from the date of original purchase. This is a no hassle warranty with no mail in warranty card needed. This warranty does not cover damages in shipment, failures caused by other products not supplied by Channel Vision Technology, or failures due to accident, misuse, abuse, or alteration of the equipment. This warranty is extended only to the original purchaser, and a purchase receipt, invoice, or other proof of original purchase date will be required before warranty repairs are provided.


Mail in service can be obtained during the warranty period by calling (800) 840-0288 toll free. A Return Authorization number must be obtained in advance and can be marked on the outside of the shipping carton.


This warranty gives you specific legal rights and you may have other rights (which vary from state to state). If a problem with this product develops during or after the warranty period, please contact Channel Vision Technology, your dealer or any factory-authorized service center.

■ CHANNEL VISION™ www.channelvision.com

234 Fischer Avenue, Costa Mesa, California 92626 USA (714)424-6500 • (800)840-0288 • (714)424-6510 fax email: techsupport@channelvision.com

INSTRUCTIONS





RS801-SA 8" Rock Speaker-Sand RS801-GR 8" Rock Speaker-Granite



Specifications: RS801-SA

Frequency range: 55Hz - 20kHz ± 3dB

Sensitivity: Sensitivity: 89 dB(1W/1m)

Power Handling: 160 Watts

Drivers: 1-1" Neodymium waterproof dome

tweeter; 1-8" PP cone woofer

Impedance: 8 ohms

Crossover: 12dB/octive (low pass)

12dB/octive (high pass)

Magnet: 20-ounce ferrite magnet

Dimensions: 15 "W x11"D x 13"H

Color: Sand

Box: Single speaker in each box

Installation:

 We recommend wiring with AWG 16 or larger, stranded wire.

For proper phasing, both speakers must be wired alike.
 Connect red wire to red terminal on speakers and to red or plus terminal on amplifier. These speakers are sold individually.

 To control the volume of the speakers locally, use an impedance matching volume control, such as the **Specifications: RS801-GR**

Frequency range: 55Hz - 20kHz ± 3dB

Sensitivity: Sensitivity: 89 dB(1W/1m)

Power Handling: 160 Watts

Drivers: 1-1" Neodymium waterproof dome

tweeter; 1-8" PP cone woofer

Impedance: 8 ohms

Crossover: 12dB/octive (low pass)

12dB/octive (high pass)

Magnet: 20-ounce ferrite magnet

Dimensions: 15 "W x11"D x 13"H

Color: Granite

Box: Single speaker in each box

Installation:

- We recommend wiring with AWG 16 or larger, stranded wire.
- For proper phasing, both speakers must be wired alike.
 Connect red wire to red terminal on speakers and to red or plus terminal on amplifier. These speakers are sold individually.
- To control the volume of the speakers locally, use an impedance matching volume control, such as the