



## Indoor Dome Color 1.3 Megapixel IP Camera

6530

Channel Vision's indoor 1.3 megapixel dome CMOS IP camera offers superior image quality and has the ability to capture images up to 1200 x 800 pixels. With H.264 compression, less bandwidth and storage space are used, while delivering full resolution at max frame rate with faster speeds over the internet.

### Features

1.3 megapixel CMOS sensor
H.264 compression, MJPEG and MPEG4 codecs
Event triggered micro SD card recording
POE Supported



### Specifications\*

**CPU:** ARM9; 32 Bit RISC  
**DDR2:** 256MB  
**Image Sensor:** 1/4" CMOS (1.3 Megapixel)  
**Sensitivity:** 1.0 lux at 30FPS  
**DC Iris:** Yes  
**Lens Type:** Fixed 4.2mm  
**Power Over Ethernet:** Supported, Designed for 802.3af Standard, 47V recommended  
**Power Consumption:** 12vDC 480mA  
**Ethernet:** 10/100 Base T  
**Network Protocol:** HTTP, HTTPS, SNMP, QoS/DSCP, Access List, IEEE, 802.1X, RTSP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UpNP, 3GPP, Samba

**Triple Streaming:** 1280x800@30fps, 1280x720@30fps, 640x480@30fps, 320x240@30fps, 176x144@30fps,  
**Triple Streaming:** Yes  
**Image Snapshot:** Yes  
**Full Screen Monitor:** Yes  
**Privacy Mask:** Yes  
**Compression:** H.264, JPEG, MPEG-4  
**Bit-rate adjustment:** CBR, VBR  
**Motion Detection:** 3 areas  
**Triggered Actions:** Mail, FTP, Save to Micro SD card; Samba  
**Security:** Password protection, IP address filtering, HTTPS encrypted data transmission 802.X port based authentication for network protection

\*Specifications subject to change



Channel Vision Central  
Structured Wiring



Channel Vision DVI  
IR & Audio Equipment



ARIA™  
Multi-Room Audio



Channel Vision Technology  
Modulators, Cameras, Intercoms