



CHANNEL VISION™ *Central*

◆ Structured Wiring Solutions ◆

C-0218 and C-0219

With our new **telephone and video distribution modules**, you can efficiently distribute four CO lines to up to 15 locations. All models feature 110 punch down connectors and compact design for easy installation into our structured wiring panels.

Features:

- Distributes 4 CO lines to 7 (C-0218) or 15 (C-0219) locations
- Simple 110 punchdown connectors
- Includes 4-way RF splitter (DC passing)
- RF input compatible 5-1000MHz, 130dB RFI
- All ports DC and IR passing
- Compact Design

Specifications:

C-0218

- RF insertion loss: 7.5 dB
- RF inputs: 1
- RF outputs: 4
- 110 connectors: 8 (bridged)
- Dimensions: 4.0”L x 6.38” W x 1.75” D

C-0219

- RF insertion loss: 7.5 dB
- RF inputs: 1
- RF outputs: 4
- 110 connectors: 16 (bridged)
- Dimensions: 5.13”L x 6.38” W x 1.75” D



C-0218



C-0219



CHANNEL VISION™

234 FISCHER AVENUE • COSTA MESA, CA 92626
(714) 424-6500 • (800) 840-0288 • (714) 424-6510 fax
www.channelvision.com • email: sales@channelvision.com