



DVR Kit with Outdoor Cameras

DVR-43GKit2

Channel Vision's DVR Kit with outdoor cameras is a full surveillance DVR kit with four outdoor IR bullet cameras (6332-0) and a 500GB drive for video recording.



DVR-43G 500GB Features

Windows and Mac compatible
Enhanced H.264E compression for recording and web compression- 20% more capacity than last generation
3G mobile phone streaming video
Internet viewing through Internet Explorer
Remote viewing Central Management System (CMS) supports up to 16 DVRs with 32 channel viewing
Real time live display on VGA and BNC video out at the same time
AVI converter transfers data with a time stamp for use as legal evidence
Motion detection with individual sensitivity adjustments for each camera
Audio in and out
Real time recording at half the D1 resolution (720 x 240)

Outdoor Camera Features (6332-0)

High Quality 1/3" Hi-Res Suped HAD II CCD
650 lines of resolution
36 IR-LED's for night viewing up to 45'
4-9mm Varifocal lens
Waterproof camera suitable for outdoor use (IP66)
3 axis adjustable camera mount

Specifications*

DVR-43G 500GB Drive:

Video System: Auto Selectable (PAL or NTSC)

Video Inputs: 4ch BNC

Video Outputs: Composite Video & VGA

Spot Output: 1ch BNC

Audio Input: 1ch RCA

Audio Output: 1ch RCA

Sensor Input: 4ch Input

Sensor Output: 1ch Relay Output

Display Divisions: 1, 4

Display Zoom: 2X to 8X

Recording Compression: Enhanced H.264

Network Frame Rate: 120 Frames per second

Recording Watermark: Yes on AVI File

Motion Sensitivity: 15 Levels

Recording Frame Rate (max): 30fps/60fps/120fps (NTSC)
25fps/50fps/100fps (PAL)

Recording Resolutions: 720x480, 720x240, 360x240 (NTSC)
720x576, 720x288, 360x288 (PAL)

Network Protocols: TCP/IP, SMTP, HTTP, DHCP, DDNS, PPPoE

6332 IR Illuminated Color Bullet Camera:

Image Sensor: Sony 1/3" Hi-Res Effio E CCD

Camera Lens: 4-9mm

Resolution: 650 lines

S/N Ratio: 50dB Min

Min Illumination: 0 LUX (IR on)

Effective Pixels: 811 x 508

Gamma Characteristic: 0.45

Sync. System: Internal, Negative sync.

Power supply: 2.1mm

Power Requirements: 12VDC 196mA (IR off)
250mA (IR on)

Video Output: 1 Vp-p @ 75 ohms

Auto Electronic Shutter: Auto, 1/50 (1/60) -
1/100,000 Sec

Waterproof Criterion: IP66

Operating Temperature: -10°C to 50°C
(14° to 122°F)

Infrared Illumination: 36 IR LEDs



Channel Vision Central
Structured Wiring



Channel Vision
IR & Audio Equipment



ARIA™
Multi-Floors Audio



Channel Vision Technology
Modulators, Cameras, Intercoms

CHANNEL VISION™

www.ChannelVision.com

800.840.0288

714.424.6500

234 Fischer Ave., Costa Mesa, CA 92626 USA

Specifications subject to change without notice.
Channel Vision Technology, Channel Vision Central and ARIA are trademarks of Channel Vision Technology
©Channel Vision Technology 2011